

BCBZ Zone 1000 Series 2.5" and 4" Digital Clock



HIGHLIGHTS

- Switch for time zone offset in one (1) hour increments
- Immediate correction for time change
- Clocks will not deviate from each other
- Available in 2.5" and 4.0" display
- Available in red or blue displays
- 12 or 24 hour format
- LEDs for visual representation of the receiving and transmitting of data
- Available in a variety of colors or custom colors
- Custom characters and letter tones available
- "BELL", "FirE" messaging capabilities
- Choice of two (2) wire digital communication protocol or RS485 protocol
- Bright LED display
- Anti-glare red or blue bezel
- No battery backup required
- Unlimited clocks can be run off the same communication line (RS485 only)
- Dynamic range for input voltages
 - 12—30 VDC (24 Volt model)
 - 12—30 VAC (24 Volt model)
 - 78—130 VAC (110 Volt model)
- Analog and digital clocks can be combined on the same power line (two (2) wire) or communication line (RS485)
- Plug in Molex connectors
- Available in 110 VAC or 24 VAC/VDC
- FCC approved
- Made in the U.S.A.

DESCRIPTION

The BCBZ Series digital zone clock has the capability to have multiple time zones on one (1) system. BCBZ Series digital clocks are available with either 2.5" or 4.0" high characters in a four (4) digit display. The BCBZ Series digital clocks are reliable slave clocks that work on Bogen two (2) wire digital communication or a RS485 protocol. The BCBZ Series is based on our high efficiency, bright LED display. The clocks implement immediate correction upon receipt of the digital signal. The BCBZ has a series of options such as 12 or 24 hour format, display "Bell" or "FirE" messages, as well as two (2) brightness settings. The BCBZ Series clock also features LEDs on the board to show if it is receiving and transmitting data, making it easier to maintain and install. The unique, specially molded anti-glare bezel gives a smooth, clean look with no visible external screws. The BCBZ Series zone clocks come in two (2) types of metal cases that can be mounted flush or surface. The BCBZ Series is FCC approved.

BCBZ Zone 1000 Series 2.5" and 4" Digital Clock

SPECIFICATIONS

- Display size: 2.5" and 4.0" characters
- Display color: Vibrant red or blue
- Visibility: 100 feet — 2.5" Clock
250 feet — 4.0" Clock
- Bezel color: Anti-glare red or blue
- Bezel size: (LxW) 4.69" x 10.31" — 2.5" Clock
6.75" x 13.31" — 4.0" Clock
- Temperature range:
 - Operating: 0°C - 45°C
 - Storage: -15°C - 75°C
- Input voltage for 2.5" clock; 12 - 30 VDC (24 Volt)
12 - 30 VAC (24 Volt)
78 - 130 VAC (110 Volt)
- Input voltage for 4.0" clock: 16 - 28 VDC (24 Volt)
14 - 28 VAC (24 Volt)
85 - 135 VAC (110 Volt)
- Average current consumption: (max brightness)
 - 2.5" Clock
85 mA @ 24 VAC
30 mA @ 110 VAC
 - 4.0" Clock
190 mA @ 24 VAC
45 mA @ 110 VAC
- Signal input: RS485 or 2 Wire Digital Communication
- Signal output: RS485
- Display format: 12 or 24 hour mode
- Brightness: 2 levels, adjustable
- Mounting dimensions: (LxWxD)
 - Flush 2.5": 16.56" x 16" x 1"
 - Flush 4": 18.44" x 19.81" x 1"
 - Surface 2.5": 16.81" x 16" x 3"
 - Surface 4": 18.38" x 19.75" x 3"
- Shipping weight: 5 lbs.
- Power kit includes: 1 - 5 pin power harness
1 - 4 pin RS485 harness
1 - grounding wire, loop end
- Compliance: FCC approved

ARCHITECTURAL AND ENGINEERING SPECIFICATIONS

The clock shall be a Bogen BCBZ Series digital clock and shall have either a full 2.5" or 4.0" high efficiency red or blue LED numeral display. The clock will be able to have multiple time zones in one (1) system. The clock shall operate as a RS485 digital slave clock or as a two (2) wire digital communication digital slave clock. The clock will have data LEDs to display the receiving or sending of data. It will be capable of having a 12 or 24 hour display format. It shall have two (2) levels of adjustable brightness and will immediately correct for time changes. The clock shall be mounted on a low profile surface or wall mount metal case. The clock shall have messaging capabilities including "BELL" and "FirE". Then the input is lost, the colon on the display of the clock shall flash. The clock bezel is to be anti-glare red or blue with a smooth surface. No external screws shall be visible on the bezel or clock housing. The clock shall be FCC approved.

MECHANICAL DRAWING

